# eDatasheet HP Elite Slice G2 - Audio Ready with Zoom Rooms (8EN91AW)



## How conferencing should be

Designed for rooms of all sizes with 3rd party AV accessories, the HP Elite Slice G2 - Audio Ready with Zoom Rooms[2] helps simplify meetings. Easily connect[3] with the Center of Room Control.

## Ready to go

Simplify your Zoom Room deployment with a compute device pre-imaged with Zoom Room software and packaged with an easy to use, moveable 12.3-inch diagonal Center of Room Control display, HDMI adapters, and a port cover.

### **One-touch collaboration**

Enjoy on-demand calling and flexible accessibility. Easily add attendees and share content with one touch of the anti-glare screen on the Center of Room Control with dual viewing angles and familiar Zoom Rooms interface.[3]

## Connect to existing audio and video[2]

Show your team in the best light and easily connect your Zoom Rooms interface systems, audio, and video peripherals to HP Elite Slice G2 - Audio Ready with Zoom Rooms.[2]

# Specifications

Form factor	Ultra-small form factor
Operating system	Windows 10 IoT Enterprise 64
Processor family	7th Generation Intel® Core™ i5 processor
Processor	Intel <sup>®</sup> Core <sup>™</sup> i5-7500T with Intel <sup>®</sup> HD Graphics 630 (2.7 GHz base frequency, up to 3.3 GHz with Intel <sup>®</sup> Turbo Boost Technology, 6 MB cache, 4 cores) <sup>[6,7]</sup>
Chipset	Intel® Q170 <sup>[27]</sup>
Memory	8 GB DDR4-2400 SDRAM (2 x 4 GB)
Memory Slots	2 DIMM
Internal Storage	128 GB PCIe <sup>®</sup> NVMe™ SSD
Graphics	Integrated
Graphics (integrated)	Intel® HD Graphics 630
Display	31.2 cm (12.3") diagonal FHD LCD touch screen (1440 x 960)
Display	12.3" diagonal FHD LCD touch screen (1440 x 960) <sup>[15]</sup>
Audio	Conexant CX7501 codec, universal audio jack that is retaskable
Minimum dimensions (W x D x H)	16.5 x 16.5 x 11.2 cm
Minimum dimensions (W x D x H)	6.5 x 6.5 x 4.4 in
Weight	1.57 kg (Exact weight depends on configuration.)
Weight	3.46 lb (Exact weight depends on configuration.)
Pointing device	HP USB Optical Mouse
Ports	1 audio-in/out; 1 USB 3.1 Type-C™
Expansion slots	1 M.2 2230; 1 M.2 2280 <sup>[8]</sup>
Ports	1 DisplayPort™; 1 HDMI; 1 power connector; 1 RJ-45; 1 USB 3.1 Type-C™ (alternate mode DP); 2 USB 3.1 Gen 1; HP Video Ingest Module with HDMI input
Package dimensions (W x D x H)	30.5 x 59.9 x 21.5 cm
Package weight	7.6 kg
Network interface	Intel® I219LM GbE
Network interface type	LAN
Network interface type	WLAN
Network interface	Intel® Dual Band Wireless-AC 8260 802.11ac (2x2) and Bluetooth® 4.2 Combo, vPro™
Power	90 W external power adapter <sup>[23]</sup>
Energy efficiency	ENERGY STAR <sup>®</sup> certified
Energy star certified	ENERGY STAR®
Management features	HP Image Assistant
Environmental	Low halogen
Security management	Active Health (black box flight recorder); HP Client Security Suite; HP Dual Head Keyed Cable Lock Kit; Infineon TPM SLB9670 1.2/2.0 (Common Criteria EAL4+ certified); Sure Start 3.0; Windows Defender <sup>[20]</sup>
Software	Absolute Persistence module; HP Notifications; HP Connection Optimizer; Zoom Rooms
Warranty	3 year (3-3-3) limited warranty and service offering includes 3 years of parts, labor and on-site repair. Includes free 24/7 telephone support. Terms and conditions vary by country. Certain restrictions and exclusions apply.
What's in the box	HP Cable and Port Cover; HP Center of Room Control; HP DisplayPort™ to HDMI True 4K Adapter; HP Elite Slice G2 - Audio Ready with Zoom Rooms; HP VESA Plate; HP Video Ingest Module <sup>[26]</sup>

# **Accessories and services**

No Recommended Accessories and Services

### **Messaging Footnotes**

[2] Audio equipment or speakers are required and sold separately.

[3] Internet connection required and sold separately.

#### **Technical Specifications Footnotes**

[6] Multi-core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering is not a measurement of higher performance. Intel, Pentium, Intel Core, Celeron, Intel logo and the Intel Inside logo are trademarks of Intel Corporation in the U.S. and other countries.

[7] Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See http://www.intel.com/technology/turboboost/ for more information.

[8] (1) M.2 2230 PCIe for WLAN; (1) M.2 2280 PCIe for NVMe SSD.

[15] Center of Room Control weight: 1.04 kg (2.3 lb); Dimensions: width (X) 30.17 cm (11.88 in), height(Y) 21.97 cm (8.65 in), depth (Z) 8.08 cm (3.17 in).

[20] Firmware TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT). TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT).

[23] All power supplies are not available in every region.

[26] HP Cable and Port Cover and HP USB Type-C<sup>™</sup> Extension Cable: only one can be installed.

[27] For full Intel® vPro<sup>™</sup> functionality, Windows, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN card and discrete TPM 2.0 are required. See http://intel.com/vpro

© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Bluetooth is a trademark of its proprietor and used by HP Inc. under license. Intel, Core and Intel vPro are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. USB Type-C<sup>™</sup> and USB-C<sup>™</sup> are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. DisplayPort<sup>™</sup> and the DisplayPort<sup>™</sup> logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. All other trademarks are the property of their respective owners.

