

1U Single-Port KVM Console for Server Rack - 19 in.

Product ID: RKCONS1901



This rack-mount KVM console provides complete keyboard, monitor and mouse control for a single server or multiple servers, connected through a separate KVM switch (sold separately). The 19 in. console installs into 1U of rack space, offering a space-efficient solution for complete console control.

Maximize your IT budget, minimize your hassle

This KVM console provides all the essential controls you'll need to manage your server room at a low cost. The console features a built-in keyboard and a touchpad for intuitive control, as well as an LCD display that supports resolutions up to 1280x1024.

Maximize your screen space

This versatile LCD console has a 19 in. screen. The increased screen space allows you to run multiple applications on the same screen, increasing your productivity.





Clutter-free monitoring

The rack-mount LCD console slides out from 1U of rack space, enabling you to easily monitor and control a single server or multiple servers when connected through a KVM switch. The rack-mount VGA console features a handle that makes it easy to slide the console in and out of the server rack, keeping your area organized and clutter-free.

Hassle-free system integration

The rack console features a single-port KVM module, which enables you to connect it directly to a server. The module offers the flexibility you need to easily integrate it into your existing server infrastructure.

The RKCONS1901 is backed by a StarTech.com 2-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility













Applications

- Control a single system, or dozens of KVM-connected computers
- Improve the internal space efficiency of your server cabinet
- Manage cabinet-mounted servers and KVM switches

Features

- Save money and reduce hassle with a cost-effective rack-mount LCD console
- Reduce your server room clutter with a 1U rack-mount design
- Large 19 in. screen allows you to run multiple applications at one time
- Intuitive system integration with direct support for a single server or KVM switch
- Built-in touchpad and keyboard
- Resolutions up to 1280x1024



Data Sheet

| | Warranty | 2 Years |
|-----------------------------|------------------------------|--|
| Hardware | Audio | No |
| | Cables Included | Yes |
| | Daisy-Chain | Yes |
| | Display Size | 19in |
| | Front Door Key Lock | No |
| | KVM Ports | 1 |
| | Number of Monitors Supported | 1 |
| | Panel Type | Active Matrix TFT LCD |
| | PC Interface | USB |
| | PC Video Type | VGA |
| | Rack-Mountable | Yes |
| | U Height | 1U |
| Performance | Brightness | 250 cd/m ² |
| | Color Depth | 8-bit, 16.7M colors |
| | Contrast Ratio | 1000:1 |
| | IP Control | No |
| | Maximum Analog Resolutions | 1280 x 1024 |
| | Maximum Number of Users | 1 |
| | MTBF | 50, 000 Hrs |
| | Pixel Pitch Support | 0.264 x 0.264 mm |
| | Supported Resolutions | 1024x768 1280x720 (High-definition 720p) 1280 x 1024 |
| | | Lower resolutions are also supported |
| Connector(s) | Console Interface(s) | 1 - VGA (15 pin, High Density D-Sub) Female Input |
| Indicators | LED Indicators | 1 - power / status LED |
| Power | Power Consumption (In Watts) | 17W |
| Environmental | Humidity | 10 ~ 80% RH |
| | Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| | Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| Physical Characteristics | Maximum Mounting Depth | 30.7 in [78 cm] |



Data Sheet

| | Minimum Mounting Depth | 19.7 in [50 cm] |
|--------------------------|---------------------------|--|
| | Product Height | 1.7 in [4.3 cm] |
| | Product Length | 21 in [53.3 cm] |
| | Product Width | 19 in [48.3 cm] |
| | Weight of Product | 27 lb [12.2 kg] |
| Packaging Information | Package Height | 7.5 in [19 cm] |
| | Package Length | 30.1 in [76.5 cm] |
| | Package Width | 24.2 in [61.5 cm] |
| | Shipping (Package) Weight | 35.4 lb [16 kg] |
| What's in the Box | Included in Package | 1 - KVM console |
| | | 1 - 6 ft [1.8 m] KVM cable |
| | | 8 - M5 cage nuts |
| | | 8 - M5 screws |
| | | 5 - regional power cords (NA, JP, UK, EU, ANZ) |
| | | 2 - mounting rails (variable length) |
| | | 1 - quick-start guide |

Product appearance and specifications are subject to change without notice.